

Copyright (c) Queen's Printer,
Victoria, British Columbia, Canada

**License
Disclaimer**

B.C. Reg. 151/2002
Insurance Corporation of British Columbia

Deposited June 21, 2002

This consolidation is current to August 31, 2021.

[Link to consolidated regulation \(PDF\)](#)

[Link to Point in Time](#)

Motor Vehicle Act

MOTOR ASSISTED CYCLE REGULATION

[includes amendments up to B.C. Reg. 56/2018, March 22, 2018]

Contents

- 1 Motors
- 2 Wheels
- 3 Motor shut-off requirement
- 4 Generators
- 5 Brake performance requirement
- 6 Drive system and equipment securement
- 7 Electrical terminals

Motors

The motors of a motor assisted cycle must

- 1 be electric motors,
 - (a) have continuous power output ratings that in total do not exceed 500
 - (b) watts, and
 - (c) not be capable of propelling the motor assisted cycle at a speed greater than 32 km/hr on level ground.

[en. B.C. Reg. 56/2018, s. 1.]

Wheels

The wheels of a motor assisted cycle must be 350 mm or more in diameter.

- 2 (1) A motor assisted cycle must not have more than 3 wheels in contact with the
- (2) ground.

Motor shut-off requirement

- 3** (1) A motor assisted cycle must be equipped with a mechanism, separate from the accelerator controller, that
- (a) allows the driver to turn the motors on and off from a normal seated position while operating the motor assisted cycle, or
 - (b) prevents the motors from turning on or engaging before the motor assisted cycle attains a speed of 3 km/hr.

- The motors of a motor assisted cycle must turn off or disengage if
- (2)
- (a) the operator stops pedaling,
 - (a) an accelerator controller is released, or
 - (b) a brake is applied.
 - (c) [am. B.C. Reg. 56/2018, s. 2.]

Generators

- A motor assisted cycle must not be equipped with a generator, alternator or similar
- 4** device powered by a combustion engine.

Brake performance requirement

- A motor assisted cycle must be equipped with brakes on all wheels or on each
- 5** (1) axle.

- The braking system must be capable of bringing the motor assisted cycle, while
- (2) being operated at a speed of 30 km/hr, to a full stop within 9 m from the point at which the brakes were applied.

Drive system and equipment securement

- The motor drive systems and all energy storage devices of a motor assisted cycle
- 6** must be secured to prevent movement in any direction relative to the motor assisted cycle while the motor assisted cycle is operating.

[am. B.C. Reg. 56/2018, s. 3.]

Electrical terminals

- All electrical terminals on a motor assisted cycle must be completely insulated or
- 7** covered.

[Provisions relevant to the enactment of this regulation: *Motor Vehicle Act*, R.S.B.C. 1996, c. 318, s. 182.1]